ASTROSE® AUTONOMOUS SENSOR NETWORK FOR CONDITION MONITORING OF POWER LINES



ASTROSE[®] Project Partners

Mitteldeutsche Netzgesellschaft Strom mbH amprion GmbH ELMOS Semiconductor AG Microelectronic Packaging Dresden GmbH K+L Elektrotechnik GmbH unilab AG Fraunhofer ENAS Fraunhofer IZM Chemnitz University of Technology

Funded by

German Federal Ministry of Education and Research (BMBF)

Coordinated by

Description

The condition monitoring of power lines aims at the optimization of the capacity utilization of energy transport while guarantee hazard free operation. The ASTROSE® system allows a decentralized monitoring of high-voltage transmission networks (110 kV, 220 kV and 380 kV) using autonomously working sensors. They measure the key parameters determining a cable's maximum throughput - the inclination of the power lines, the temperature, the current flow and the wind movement. An ultra-low power micro controller collects the data from the sensors and controls the radio transceiver for the wireless communication in the 2.4 GHz ISM frequency band.

Every 15 minutes, all data are wirelessly transmitted along the power line to the transformer station. There the data are fed in an internet-based remote maintenance system. Each sensor node is geographically localized and identified by its unique ID. The housing of the sensor node is made of PUR (Polyurethan). It contains the electronics, sensors, antennas and the antenna filter. All components are powered by the current of the electrical fringing field that surrounds the conductor wires. A capacitive MEMS inclination sensor detects both, the sag of the power line and its oscillation caused by wind motion. In order to avoid partial discharges slot antennas are used that distribute the 50 Hz electric field. The antenna filter avoids the influence of interfering signals caused by partial discharge.

> station with integration control station

> > unilab 🛛










eless communication



ASTROSE® Sensor Node – Specifications

Description	Value	Unit
Casing diameter	100	mm
Casing length	150	mm
Measurement range of the inclination sensor	± 10	o
Resolution of the inclination sensor	0.01	o
Measurement range of the oscillation sensor	± 90	o
Resolution of the oscillation sensor	0.1	o
Measurement range of the current sensor	0 4	kA
Resolution of the current sensor	10	А
Short-circuit detection	> 4	kA
Measurement range of the temperature sensor	-25 100	°C
Resolution of the temperature sensor	0.1	°C
Temperature sensor accuracy	± 1	°C

Base Station – Specifications

Description	Value	Unit
Dimensions (L x W x H)	130 x 80 x 20	mm³
Operation voltage	9	V
Wireless data coupling via 50 Ohm antenna socket (SMA-compatible outdoor beam antenna included)	1	
Communication interface (RS232, fiber optic)	1	

Contact

Fraunhofer ENAS

Fraunhofer Institute for Electronic Nano Systems Technologie-Campus 3 09126 Chemnitz, Germany

Contact person

Dr. Steffen Kurth Phone: +49 371 45001-255 E-mail: steffen.kurth@enas.fraunhofer.de

Fraunhofer IZM

Fraunhofer Institute for Reliability and Microintegration Gustav-Meyer-Allee 25 13355 Berlin, Germany

Contact person

Dr. Volker Großer Phone: +49 30 46403-250 E-mail: volker.grosser@izm.fraunhofer.de

Photo acknowledgments: MEV Verlag, Fraunhofer ENAS All information contained in this datasheet is preliminary and subject to change. Furthermore, the described system is not a commercial product.



IZM









